


12-20 WATT HYBRID

POINT OF LOAD DC-DC REGULATORS

PROTON RAD HARD 100K+[®] TECHNOLOGY



Features

- Rad Hard: TID > 100kRad(Si)
- 2:1 margin: Operates beyond 200kRad TID
- No SEE:LET > 82MeV*cm²/mg
- Proton Resistant: No optocouplers used
- Synchronous rectification for high efficiency
- Non-isolated for intermediate bus applications
- Adjustable output voltage trim
- Thick Film Hybrid DC-DC Regulator
- Inhibit function
- 100kHz operation
- Sync input 1:1, 95-105 kHz
- Full hermetic package, solder seal and seam welded; PC and Chassis mount options
- Remote Sense

Specifications

INPUT: 5 VDC nominal

Range: 4.6 to 5.4 VDC continuous

ISOLATION:

Input-Output: Non-Isolated

Input and Output to case: 100 VDC

OUTPUT:

External capacitance recommended for specified performance

ENVIRONMENT:

Storage temperature: -55°C to +150°C

Shock: 50 G's

Acceleration: 500 G's

Vibration: 30 G's

Grades EU, R & S:

Full Output Power at T_{case} = +85°C

Linearly derates to zero at

T_{case} = +115°C

Grades RE & SE:

Full Power Output at T_{case} = +125°C

Linearly derates to zero at

T_{case} = +135°C

WEIGHT: 50 grams typical

SERIES 5087

POSITIVE OUTPUT CONVERTERS		5087-P01 (12W)			5087-P01.2 (14W)			5087-P01.5 (18W)		
PARAMETER	CONDITION	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX
Output voltage	(Trim Range)	+0.95	+1.0	+1.05	+1.15	+1.2	+1.25	+1.4	+1.5	+1.6
Output current	V _{in min} — V _{in max}	—	—	12A	—	—	12A	—	—	12A
Efficiency	P _{out} = max rated load	—	78%	—	—	81%	—	—	81%	—
Line regulation	P _{out} = max rated load V _{in min} — V _{in max}	—	10mV	30mV	—	10mV	30mV	—	10mV	30mV
Load regulation	P _{out} = 10% to F.L.	—	10mV	30mV	—	10mV	30mV	—	10mV	30mV
Output ripple	F.L. BW 2 MHz mV _{pp}	—	20	—	—	20	—	—	20	—
External Output Cap	(μF)	1000	—	4000	1000	—	4000	1000	—	4000
POSITIVE OUTPUT CONVERTERS		5087-P01.8 (20W)			5087-P02.0 (20W)			5087-P02.5 (20W)		
Output voltage	(Trim Range)	+1.7	+1.8	+1.9	+1.9	+2.0	+2.1	+2.4	+2.5	+2.6
Output current	V _{in min} — V _{in max}	—	—	11A	—	—	10A	—	—	8A
Efficiency	P _{out} = max rated load	—	82%	—	—	83%	—	—	84%	—
Line regulation	P _{out} = max rated load V _{in min} — V _{in max}	—	10mV	50mV	—	10mV	50mV	—	20mV	100mV
Load regulation	P _{out} = 10% to F.L.	—	10mV	50mV	—	10mV	50mV	—	20mV	100mV
Output ripple	F.L. BW 2 MHz mV _{pp}	—	20	—	—	20	—	—	25	—
External Output Cap	(μF)	1000	—	4000	1000	—	4000	1000	—	4000
POSITIVE OUTPUT CONVERTERS		5087-P03.3 (20W)								
Output voltage	(Trim Range)	+3.2	+3.3	+3.4						
Output current	V _{in min} — V _{in max}	—	—	6A						
Efficiency	P _{out} = max rated load	—	89%	—						
Line regulation	P _{out} = max rated load V _{in min} — V _{in max}	—	25mV	125mV						
Load regulation	P _{out} = 10% to F.L.	—	25mV	125mV						
Output ripple	F.L. BW 2 MHz mV _{pp}	—	30	—						
External Output Cap	(μF)	1000	—	4000						
Model No.	Case Style	Pin Count	Mounting							
5087 UF	8	12	Seam Weld Chassis Mount with Flange							

Pin Outs

Pin 1 Positive Input	Pin 7 V ref
Pin 2 Positive Input	Pin 8 Adjust
Pin 3 Input/Output Common	Pin 9 I out
Pin 4 Output	Pin 10 Sync Input
Pin 5 Output	Pin 11 Remote Sense+
Pin 6 Case Ground	Pin 12 Inhibit

Case Dimensions

Units: inches | millimeters

Case Style	UF
A	2.160 54.864
B	1.510 38.354
C	0.495 12.573
D	— —
E	1.600 40.640
F	2.890 73.406
G	2.550 64.770

CASE STYLE 8

